

GENERAL NOTES:

1. STEEL PLATES, SHAPES AND BARS SHALL BE WEATHERING STEEL. WELD ALL JOINTS. CONSTRUCT THE AIRFLOW CLOSURE ASSEMBLY TO ELIMINATE SURFACES ON WHICH MOISTURE OR DEBRIS CAN BE TRAPPED. PLIES OF MATERIAL SHALL BE TIGHT TO PREVENT THE INCURSION OF MOISTURE. ALL TUBULAR MEMBERS SHALL BE HERMETICALLY SEALED TO PREVENT THE INCURSION OF MOISTURE, EXCEPT AS OTHERWISE NOTED. ROUND OR CHAMFER ALL EXPOSED SHARP CORNERS AND EDGES.

ABANDONED MINE LAND PROGRAM MINING AND MINERALS DIVISION ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

SCALE: 3/4" = 1'-0" EMPORIA LODE DATE: MARCH 14, 2006

DRAWN BY: JAK/JRS REVISED:

AIRFLOW CLOSURE DETAILS AT FEATURE 047-034S SHAFT

LAKE VALLEY MINE SAFEGUARD PROJECT - PHASE II FIGURE 34