



047-040ST POWDER HOUSE MESH.DWG PLOT SCALE 1 = 48

- GENERAL NOTES:**
1. THE LOCATION AND DIMENSIONS INDICATED FOR THE STEEL MESH ARE APPROXIMATE. ADJUST AS REQUIRED FOR FIELD CONDITIONS.
  2. THE ROCK ANCHOR LOCATIONS INDICATED ARE PRELIMINARY. ADJUST LOCATIONS AND NUMBER OF ANCHORS TO FIT FIELD CONDITIONS. ANCHORS SHALL BE SPACED NO MORE THAN TWELVE FEET FROM THE NEAREST ANCHOR. LOCATE ANCHORS, TO AVOID THE UNDERGROUND VOID AND THIN ROCK AT ENTRANCE DOOR, AT MESH INSTALLATION CORNERS, ALONG MESH EDGES NEAR PANEL OVERLAPS, AND AS REQUIRED TO SNUG THE MESH ONTO THE GROUND SURFACE.
  3. MINIMIZE SITE DISTURBANCE. TRIM EXISTING SHRUBS TWO TO SIX INCHES ABOVE GROUND SURFACE TO PLACE MESH. PLACE SOIL FILL AS SHOWN ON BENCH ABOVE VOID.
  4. WHERE THE STEEL MESH IS PLACED OVER THE EXISTING GROUND, COVER THE MESH WITH AT LEAST TWO INCHES OF NATIVE SOIL AND/OR WASTE ROCK MATERIAL.

**CAUTION -** THIS PROJECT REQUIRES CONSTRUCTION WORK IN, AROUND, AND OVER HAZARDOUS AND UNPROTECTED MINE SHAFTS, STOPES, ADITS, AND OTHER OPENINGS WHICH MAY BE OPEN TO THE SURFACE OR HIDDEN FROM VIEW BY TRASH, DEBRIS, OR THIN AND UNSTABLE LAYERS OF SURFACE MATERIALS OR ROCK. THE CONSTRUCTOR SHALL BE RESPONSIBLE FOR THOROUGHLY INVESTIGATING THE SITE CONDITIONS AND SCHEDULING HIS EQUIPMENT, EQUIPMENT OPERATIONS, PERSONNEL, AND SAFETY PROCEDURES TO PREVENT ACCIDENTS AND INJURIES.

<b>ABANDONED MINE LAND PROGRAM MINING AND MINERALS DIVISION</b>		
ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT		
SCALE: 1/4" = 1'-0"	EMPORIA LODE	DRAWN BY: JRS
DATE: OCT. 20, 2006		REVISED:
<b>STEEL MESH CLOSURE AT FEATURE 047-040ST POWDER HOUSE</b>		
LAKE VALLEY MINE SAFEGUARD PROJECT - PHASE II		DRAWING NUMBER: <b>FIGURE 37</b>